§ 745.65

Field Collection of Soil Samples for Lead Determination by Atomic Spectrometry Techniques," or equivalent method.

Weighted arithmetic mean means the arithmetic mean of sample results weighted by the number of subsamples in each sample. Its purpose is to give influence to a sample relative to the surface area it represents. A single surface sample is comprised of a single subsample. A composite sample may contain from two to four subsamples of the same area as each other and of each single surface sample in the composite. The weighted arithmetic mean is obtained by summing, for all samples, the product of the sample's result multiplied by the number of subsamples in the sample, and dividing the sum by the total number of subsamples contained in all samples. For example, the weighted arithmetic mean of a single surface sample containing 60 µg/ft², a composite sample (three subsamples) containing 100 µg/ft2, and a composite sample (4 subsamples) containing 110 $\mu g/ft^2$ is 100 $\mu g/ft^2.$ This result is based on the equation [60+(3*100)+(4*110)](1+3+4).

Window trough means, for a typical double-hung window, the portion of the exterior window sill between the interior window sill (or stool) and the frame of the storm window. If there is no storm window, the window trough is the area that receives both the upper and lower window sashes when they are both lowered. The window trough is sometimes referred to as the window "well."

Wipe sample means a sample collected by wiping a representative surface of known area, as determined by ASTM E1728, "Standard Practice for Field Collection of Settled Dust Samples Using Wipe Sampling Methods for Lead Determination by Atomic Spectrometry Techniques, or equivalent method, with an acceptable wipe material as defined in ASTM E 1792, "Standard Specification for Wipe Sampling Materials for Lead in Surface Dust."

§ 745.65 Lead-based paint hazards.

- (a) Paint-lead hazard. A paint-lead hazard is any of the following:
- (1) Any lead-based paint on a friction surface that is subject to abrasion and

where the lead dust levels on the nearest horizontal surface underneath the friction surface (e.g., the window sill, or floor) are equal to or greater than the dust-lead hazard levels identified in paragraph (b) of this section.

- (2) Any damaged or otherwise deteriorated lead-based paint on an impact surface that is caused by impact from a related building component (such as a door knob that knocks into a wall or a door that knocks against its door frame.
- (3) Any chewable lead-based painted surface on which there is evidence of teeth marks.
- (4) Any other deteriorated lead-based paint in any residential building or child-occupied facility or on the exterior of any residential building or child-occupied facility.
- (b) Dust-lead hazard. A dust-lead hazard is surface dust in a residential dwelling or child-occupied facility that contains a mass-per-area concentration of lead equal to or exceeding 40 $\mu g/ft^2$ on floors or 250 $\mu g/ft^2$ on interior window sills based on wipe samples.
- (c) Soil-lead hazard. A soil-lead hazard is bare soil on residential real property or on the property of a child-occupied facility that contains total lead equal to or exceeding 400 parts per million ($\mu g/g$) in a play area or average of 1,200 parts per million of bare soil in the rest of the yard based on soil samples.
- (d) Work practice requirements. Applicable certification, occupant protection, and clearance requirements and work practice standards are found in regulations issued by EPA at 40 CFR part 745, subpart L and in regulations issued by the Department of Housing and Urban Development (HUD) at 24 CFR part 35, subpart R. The work practice standards in those regulations do not apply when treating paint-lead hazards of less than:
- (1) Two square feet of deteriorated lead-based paint per room or equivalent,
- (2) Twenty square feet of deteriorated paint on the exterior building, or
- (3) Ten percent of the total surface area of deteriorated paint on an interior or exterior type of component with a small surface area.